

Huebsch is the answer.



**OPL
25-35 lb DryStar™ Tumble Dryers
and 30-45 lb TwinStar™
Stack Tumble Dryers**



25-35 lb Tumble Dryers and 30-45 lb Stack Tumble Dryer Specifications

| Models | HT025 | HT030 | HTT30 | HT035 | HTT45 |
|------------------------------------|--|---|--|---|---|
| Control Options | Micro-Display (OM), Dual Digital (QT) | Micro-Display (OM), Dual Digital (QT) | Dual Digital (QT) | Micro-Display (OM), Dual Digital (QT) | Dual Digital (QT) |
| Dry Weight Capacity - lb (kg) | 25 (11.3) | 30 (13.6) | 2 x 30 (13.6) | 35 (15.9) | 2 x 45 (20.4) |
| Width - in (mm) | 28" (711) | 28" (711) | 31 1/2" (800) | 31 1/2" (800) | 34 1/2" (876) |
| Depth - in (mm) | 40 7/8" (1038) | 46 7/8" (1191) | 42 3/4" (1086) | 46 7/8" (1191) | 48 5/8" (1235) |
| Height - in (mm) | 63 7/8" (1622) | 63 7/8" (1622) | 76 1/4" (1937) | 63 7/8" (1622) | 81 1/16" (2059) |
| Cylinder Depth - in (mm) | 24" (610) | 30" (762) | 26" (660) | 30" (762) | 30" (762) |
| Cylinder Diameter - in (mm) | 26 1/2" (673) | 26 1/2" (673) | 30" (762) | 30" (762) | 33" (838) |
| Cylinder Volume - cu. ft. (liters) | 7.7 (217) | 9.6 (271) | 10.6 (301) | 12.3 (347) | 14.8 (421) |
| Door Opening Size - in (mm) | 22 11/16" (576) | 22 11/16" (576) | 22 11/16" (576) | 22 11/16" (576) | 26 7/8" (683) |
| Airflow - cfm (liters/sec.) | 50 Hz: 430 (203) 60 Hz: 500 (236) | 50 Hz: 430 (203) 60 Hz: 500 (236) | 50 Hz: 340 (160) 60 Hz: 400 (189) | 50 Hz: 550 (260) 60 Hz: 650 (307) | 50 Hz: 500 (236) 60 Hz: 600 (283) |
| Energy Data | Gas Models: 50 Hz: 64,000 Btu/hr (18.8 kW) 60 Hz: 64,000 Btu/hr (18.8 kW) Steam Models: At 100 psi (6.9 bar): 3.9 BHP 135,000 Btu/hr (39.6 kW) Electric Models: 12 kW | Gas Models: 50 Hz: 73,000 Btu/hr (21.4 kW) 60 Hz: 73,000 Btu/hr (21.4 kW) Steam Models: At 100 psi (6.9 bar): 3.9 BHP 135,000 Btu/hr (39.6 kW) Electric Models: 21 kW | Gas Models: 50 Hz: 73,000 Btu/hr (21.4 kW) per pkct 60 Hz: 73,000 Btu/hr (21.4 kW) per pkct Steam Models: At 100 psi (6.9 bar): 3.2 BHP 111,000 Btu/hr (32.5 kW) Electric Models: 21 kW | Gas Models: 50 Hz: 90,000 Btu/hr (26.4 kW) 60 Hz: 90,000 Btu/hr (26.4 kW) Steam Models: At 100 psi (6.9 bar): 3.8 BHP 166,000 Btu/hr (48.6 kW) Electric Models: 24 kW | Gas Models: 50 Hz: 87,000 Btu/hr (25.5 kW) per pkct 60 Hz: 95,000 Btu/hr (27.8 kW) per pkct Steam Models: N/A Electric Models: N/A |
| Electrical Specifications | Gas and Steam 100/200-220/60/1 200/60/1 120/208-240/60/1 208-240/60/1 200-208/240/60/3 380/60/3 460-480/60/3 100/200/50/1 200/50/1 230-240/50/1 200/50/3 230-240/50/3 380/400-415/50/3 Electric* 208/60/1 240/60/1 200/60/1 200-208/60/3 240/60/3 380/60/3 460-480/60/3 200/50/1 230-240/50/1 200/50/3 230-240/50/3 380/50/3 400-415/50/3 | Amps: 11.0/5.8 N/A 12.0/6.7 N/A 3.2/3.2 1.5 1.6 12.1/7.5 N/A 7.5 2.9 3.5 1.5/1.6 108 94 108 62 54 33 27 105 95 60 55 33 31 | Amps: 22.0/11.6 total N/A 16.0/8.0 total N/A 6.4/6.4 total 3.0 total 3.3 total 24.2/15.0 total N/A 15.0 total 5.8 total 7.0 total 3.0/3.2 total N/A N/A N/A 124 total 108 total 66 total 54 total N/A N/A 120 total 110 total 66 total 62 total | Amps: 11.0/5.8 N/A 12.0/6.7 N/A 3.2/3.2 1.5 1.6 12.1/7.5 N/A 7.5 2.9 3.5 1.5/1.6 122 107 122 71 62 38 31 119 108 65 62 38 35 | Amps: N/A 11.2 total N/A 12.0 total 9.6/9.6 total N/A N/A N/A 11.2 total 10.8 N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A |
| Plumbing Connections - in | Gas Models: 1/2" - NPT Steam Models: 3/4" - NPT | Gas Models: 1/2" - NPT Steam Models: 3/4" - NPT | Gas Models: 1/2" - NPT Steam Models: 3/4" - NPT | Gas Models: 1/2" - NPT Steam Models: 3/4" - NPT | Gas Models: 1/2" - NPT Steam Models: N/A |
| Shipping Dimensions | Width 30" (762) Depth 43" (1092) Height 69" (1753) | 30" (762) 49" (1245) 69" (1753) | 32 1/2" (825) 47" (1194) 81" (2057) | 33" (838) 49" (1245) 69" (1753) | 35 1/2" (902) 54" (1372) 85" (2159) |
| Net Weight - lb (kg) | 299 (135) | 331 (150) | 544 (247) | 361 (164) | 673 (305) |
| Shipping Weight - lb (kg) | 332 (151) | 364 (165) | 582 (264) | 394 (179) | 718 (326) |
| Agency Approvals | cCSA _{US} , CE, CSA Star, CSA Flame | cCSA _{US} , CE, CSA Star, CSA Flame | cCSA _{US} , CE, CSA Star, CSA Flame | cCSA _{US} , CE, CSA Star, CSA Flame | cCSA _{US} , CE, CSA Star, CSA Flame |

Tumble dryer models are made to suit a variety of electrical service characteristics. See your Huebsch distributor for specifications. For further details on installation, refer to Installation, Operation and Maintenance instructions supplied with the tumble dryer. USA and Canada models are certified by C.S.A International.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

Printed in the U.S.A. ©Copyright 2011 Alliance Laundry Systems LLC

Alliance Laundry Systems, Shepard Street, Ripon, WI 54971 Telephone: 1-800-553-5120