



The Proven Performer in Laundry

SPEED QUEEN® ON-PREMISES LAUNDRY SOLUTIONS

Stacked Washer-Extractor/Tumble Dryers

SST30

2×30 lb (13 kg)

SST50

2×50 lb (25 kg)

Maximize Time and Space

Speed Queen's stacked washer-extractor/tumble dryer is a unique product that truly delivers increased productivity.

- Ideal for small OPL settings with limited space
- Increases wash capacity
- Improves throughput
- Minimal front fasteners give quick access to key washer-extractor components to improve serviceability
- Supports a higher volume than typical retail and light commercial products are able to support
- More than double production with higher capacity and faster wash times
- Reliability and durability that drastically outperforms retail or light commercial options

 3 Year
Warranty

See Speed Queen Warranty Bond for specifics.



Stacked Washer-Extractor/Tumble Dryers

| | | SST30 | | SST50 | | |
|---|------------------|--------------------|----------------------|------------------|-----------------------|----|
| | | Washer-Extractor | Tumble Dryer | Washer-Extractor | Tumble Dryer | |
| Control Option | | OPL Touch | | OPL Touch | | |
| Capacity - lb (kg) | | 30 (13) x 2 | | 50 (25) x 2 | | |
| Overall Width - in (mm) | | 31.4 (797) | | 34.4 (875) | | |
| Overall Depth - in (mm) | | 45.5 (1152) | | 51.3 (1302) | | |
| Overall Height - in (mm) | | 79.7 (2023) | | 84.3 (2141) | | |
| Cylinder Diameter - in (mm) | | 24.0 (610) | 30.0 (762) | 26.3 (668) | 33.0 (838) | |
| Cylinder Depth - in (mm) | | 16.0 (406) | 26.0 (660) | 20.3 (515) | 30.0 (762) | |
| Cylinder Volume - cu. ft (liters) | | 4.2 (119) | 10.6 (300) | 6.3 (178) | 14.8 (419) | |
| Reversing Cylinder | | - | Standard | - | Standard | |
| Door Opening Size - in (mm) | | 14.3 (363) | 22.6 (574) | 16.3 (414) | 26.9 (683) | |
| Door Bottom to Floor - in (mm) | | 14.0 (356) | 51.3 (1303) | 14.6 (370) | 52.3 (1328) | |
| Water Inlet Connection - in (mm) | | 2 x 0.75 (19) | - | 2 x 0.75 (19) | - | |
| Drain Diameter - in (mm) | | 1 x 3 (76) | - | 1 x 3 (76) | - | |
| Drain Height to Floor - in (mm) | | 4.3 (108) | - | 4.5 (115) | - | |
| Heat Input Power - Btu/hr (kW, Mj/hr.) | | - | 73,000 (21.4, 77.0) | - | 95,000 (27.8, 100) | |
| Gas Connection - in | | - | 1/2 NPT | - | 1/2 NPT | |
| Air Outlet - in (mm) | | - | 8.0 (200) Elliptical | - | 10.0 (250) Elliptical | |
| Airflow - cfm (l/sec) | | - | 400 (190) | - | 600 (285) | |
| Motor - HP (kW) | Fan | - | 0.5 (0.4) | - | 0.5 (0.4) | |
| | Drive | 1 (0.75) | 0.3 (0.2) | 2 (1.5) | 0.5 (0.4) | |
| Total # of Speeds | | 6 | - | 6 | - | |
| Cylinder Speeds - RPM (G-Force) | Gentle | 34 (0.4) | - | 33 (0.4) | - | |
| | Wash | 48 (0.8) | - | 46 (0.8) | - | |
| | Distribution | 86 (2.5) | - | 82 (2.5) | - | |
| | Very Low | 282 (27) | - | 269 (27) | - | |
| | Low | 485 (80) | - | 464 (80) | - | |
| | Medium | 542 (100) | - | 518 (100) | - | |
| Electrical Specs - amps | Gas | | | | | |
| | X | 200-240V/50/60/1/3 | 15 | 10 | 15 | 10 |
| | B | 100-120V/50/60/1 | 15 | 15 | - | - |
| | Electric | | | | | |
| | D | 200-208V/50/60/1 | 15 | 60 | - | - |
| | E | 230-240V/50/60/1 | 15 | 50 | - | - |
| | F | 200-208V/50/60/3 | 15 | 80 | - | - |
| G | 230-240V/50/60/3 | 15 | 70 | - | - | |
| Shipping Dimensions Approx. - in (mm) | Width | 34.5 (876) | | 35.5 (902) | | |
| | Depth | 47.0 (1194) | | 54.0 (1372) | | |
| | Height | 83.0 (2108) | | 89.0 (2261) | | |
| Net Weight - lb (kg) | | 770 (349) | | 910 (413) | | |
| Shipping Weight - lb (kg) | | 787 (357) | | 930 (422) | | |
| Agency Approvals | | UL _{us} | CSA | UL _{us} | CSA | |

For the most accurate information, the installation guide should be used for all design and construction purposes.
 Due to continuous product improvements, design and specifications subject to change without notice.
 The quality management systems at Alliance Laundry Systems are registered to ISO 9001.