

## On- Premises 20-100 lb Hardmount Washer-Extractor



Maximized throughput, minimized costs. That's what busy on-premises laundries demand. Huebsch® hardmount washer-extractors deliver those results, while producing exceptional finished wash quality. In addition, their durability ensures the machines will be consistent laundry performers for years to come.

### Strength

Our computer-optimized, heavy-duty frame is lighter, lasts longer, balances loads more efficiently, and reduces sound and vibration levels. Huebsch washer-extractors also boast two triple-lip seals and an excluder-face seal for seven layers of bearing protection.

### Power

Proprietary inverter-drive technology provides smooth, reliable power, saving you 33% on electricity while maximizing cleaning power. Our inverter also exerts 200 G-Force extraction to remove more moisture from loads and reduce drying time.

### Performance

Available in a variety of capacities, including 20 lb, 30 lb, 40 lb, 60 lb, 80 lb and 100 lb capacities, Huebsch cabinet hardmount washer-extractors also offer a variety of control options to match your operation's unique requirements.



### Galaxy™ with eBoost™

Customize your washing power with the ability to choose between three water levels while eliminating wasted water with advanced leak detection. PC programming, audit data retrieval and advanced diagnostics save time, while 200 G-Force extraction speeds reduce drying time and utility consumption.

visit [huebsch.com](http://huebsch.com)

# On-Premises Hardmount Washer/Extractor Specifications

MODEL	HCT020	HCT030	HCT040	HCT060	HCT080	HCT100		
CONTROL OPTION	Galaxy	Galaxy	Galaxy	Galaxy	Galaxy	Galaxy		
CAPACITY - lb (kg)	20 (9)	30 (13.6)	40 (18)	60 (27)	80 (36)	100 (45)		
OVERALL WIDTH - in (mm)	26 (660)	29 (737)	30 5/8 (778)	34 1/16 (865)	41 1/2 (1054)	41 1/2 (1054)		
*OVERALL DEPTH - in (mm)	30 1/4 (767)	34 9/16 (878)	39 3/4 (1009)	42 9/16 (1081)	48 1/2 (1234)	52 1/2 (1336)		
OVERALL HEIGHT - in (mm)	43 (1092)	45 (1142)	47 1/4 (1199)	49 7/8 (1267)	56 3/16 (1426)	56 3/16 (1426)		
CYLINDER DIAMETER - in (mm)	21 (533)	24 (610)	26 1/4 (667)	30 (762)	36 (916)	36 (916)		
CYLINDER DEPTH - in (mm)	13 3/4 (349)	16 (406)	20 1/4 (514)	22 (559)	22 (559)	26 (610)		
CYLINDER VOLUME - cu. ft. (liters)	2.76 (78.1)	4.19 (118)	6.34 (180)	9.0 (255)	12.4 (354)	13.5 (434)		
DOOR OPENING SIZE - in (mm)	11 5/8 (295)	14 5/16 (364)	16 1/4 (413)	16 1/4 (413)	18 1/2 (470)	18 1/2 (470)		
DOOR BOTTOM TO FLOOR - in (mm)	14 3/8 (365)	14 (356)	14 1/2 (368)	14 15/16 (379)	17 15/16 (455)	17 15/16 (455)		
WATER INLET CONNECTION - in (mm)	2 x 3/4 (19)	2 x 3/4 (19)	2 x 3/4 (19)	2 x 3/4 (19)	2 x 3/4 (19)	2 x 3/4 (19)		
DRAIN DIAMETER - in (mm)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)		
DRAIN HEIGHT TO FLOOR - in (mm)	4 1/2 (114)	4 1/2 (114)	4 13/16 (122)	4 11/16 (119)	5 3/4 (145)	5 3/4 (145)		
MOTOR POWER CONSUMPTION - hp (kw)	1 (.75)	1 (.75)	2 (1.7)	3 (2.2)	5 (3.7)	5 (3.7)		
TOTAL # OF SPEEDS	6, 9	6, 9	6, 9	6, 9	6, 9	6, 9		
CYLINDER SPEEDS - RPM (G-FORCE)	Gentle	37 (0.4)	34 (0.4)	33 (0.4)	31 (0.4)	28 (0.4)	28 (0.4)	
	Wash	51 (.8)	48 (.8)	46 (.8)	43 (.8)	39 (.8)	39 (.8)	
	Distribution	92 (2.5)	86 (2.5)	82 (2.5)	77 (2.5)	70 (2.5)	70 (2.5)	
	Very Low	301 (27)	282 (27)	269 (27)	252 (27)	230 (27)	230 (27)	
	Low	518 (80)	485 (80)	464 (80)	434 (80)	396 (80)	396 (80)	
	Medium	580 (100)	542 (100)	518 (100)	485 (100)	443 (100)	443 (100)	
	** High	648 (120)	606 (120)	579 (120)	542 (120)	495 (120)	495 (120)	
	**Very High	710 (150)	664 (150)	635 (150)	594 (150)	542 (150)	542 (150)	
	**Ultra High	819 (200)	766 (200)	733 (200)	686 (200)	626 (200)	568 (165)	
*** VOLTAGE/ CIRCUIT BREAKER - FLA	X	200-208/220-240/50/60/1/3	15-8	20-16	20-16	15-10 (1 Ph) 15-6 (3 Ph)	15-12 (1 Ph) 15-8 (3 Ph)	20-16 (1 Ph) 15-10 (3 Ph)
		N	440-480/50/60/3	15-4 (1 Ph) 15-3 (3 Ph)	15-6 (1 Ph) 15-4 (3 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	15-4	15-5
			15-2	15-3	15-3			
	SHIPPING DIMENSIONS APPROX. - in (mm)		Width	28 (711)	31 1/2 (800)	32 1/2 (826)	37 1/2 (953)	44 (1118)
		Depth	33 13/16 (859)	38 5/16 (973)	43 1/2 (1105)	46 15/16 (1191)	54 1/2 (1384)	58 1/2 (1486)
		Height	48 7/16 (1229)	51 5/16 (1303)	53 5/8 (1361)	56 5/16 (1430)	58 5/8 (1488)	58 5/8 (1488)
NET WEIGHT - lb (kg)			335 (152)	460 (209)	550 (249)	695 (315)	1210 (549)	1260 (572)
SHIPPING WEIGHT - lb (kg)			365 (166)	495 (225)	590 (268)	745 (338)	1260 (572)	1310 (594)
****AGENCY APPROVALS			cULus	cULus	cULus	cULus	cULus	cULus

Information shown applies to highest end control available.  
 Note: Not all options are available for all models. Twelfth digit in model number indicates US or Canadian unit. C=Canada & T=US.

Refer to the price list for the available models and options.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous improvements. Design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.

**Huebsch Distributor DC, DE, MD, PA, VA & WV**



**LES**  
 Laundry Equipment Services

**Call us Mon-Fri 8 AM - 5 PM**  
**1-800-866-6905**  
**Email: info@leslaundry.com**