



On-Premises 25 lb - 75 lb Tumble Dryer

Our single-pocket tumble dryers* feature concentrated airflow and sealed cylinder rims to ensure energy savings. This superior drying performance helps laundries maximize throughput to meet the daily workload every time. Our tumble dryers are designed with fewer moving parts, so you'll face less maintenance and wear and tear.

Efficient

High-performance heater box increases energy efficiency and reduces drying times to help on-premises laundries increase throughput, while decreasing operating costs.

Spacesaver

The 55 lb (24.9 kg) capacity model fits through a 36 in (914 mm) door opening and is 10 in (251 mm) shorter than our 50 lb (22.7 kg) unit, making it an option for laundries with limited space.

Performance

Available in 25 lb, 30 lb, 35 lb, 50 lb, 55 lb, 75 lb, 120 lb, 170 lb and 200 lb capacities, there's a tumble dryer to meet the needs of any on-premises laundry.



Galaxy™

The Galaxy Control offers the flexibility of 30 programmable cycles combined with the accuracy of our moisture-sensing technology saving time and energy increasing the life of your linens, saving time and energy.



Dual Digital

With features including one-touch cycle repeat, automatic extended tumble and a large digital countdown display, it's simple to set your drying time, temperature and cool down with the Dual Digital Control.

On-Premises 25 lb - 75 lb Dryer Specifications

| MODEL | HT025 | MODEL | HT030 | MODEL | HT035 | MODEL | HT050 | |
|---|---------------------------|---|---------------------------|---|---------------------------|---|-------------------------|---|
| CONTROL OPTION | Galaxy, Dual Digital | CONTROL OPTION | Galaxy, Dual Digital | CONTROL OPTION | Galaxy, Dual Digital | CONTROL OPTION | Galaxy, Dual Digital | |
| CAPACITY - lb (kg) | 25 (11) | CAPACITY - lb (kg) | 30 (14) | CAPACITY - lb (kg) | 35 (16) | CAPACITY - lb (kg) | 50 (23) | |
| OVERALL WIDTH - in (mm) | 279 (710) | OVERALL WIDTH - in (mm) | 279 (710) | OVERALL WIDTH - in (mm) | 315 (800) | OVERALL WIDTH - in (mm) | 38.5 (980) | |
| OVERALL DEPTH - in (mm) | 39.4 (1000) | OVERALL DEPTH - in (mm) | 45.5 (1155) | OVERALL DEPTH - in (mm) | 45.5 (1155) | OVERALL DEPTH - in (mm) | 46.8 (1190) | |
| OVERALL HEIGHT - in (mm) | 63.9 (1625) | OVERALL HEIGHT - in (mm) | 63.9 (1625) | OVERALL HEIGHT - in (mm) | 63.9 (1625) | OVERALL HEIGHT - in (mm) | 77.3 (1960) | |
| CYLINDER DIAMETER - in (mm) | 26.5 (673) | CYLINDER DIAMETER - in (mm) | 26.5 (673) | CYLINDER DIAMETER - in (mm) | 30 (762) | CYLINDER DIAMETER - in (mm) | 37 (940) | |
| CYLINDER DEPTH - in (mm) | 24 (610) | CYLINDER DEPTH - in (mm) | 30 (762) | CYLINDER DEPTH - in (mm) | 30 (762) | CYLINDER DEPTH - in (mm) | 30 (762) | |
| CYLINDER VOLUME - cu. ft. (liters) | 7.7 (220) | CYLINDER VOLUME - cu. ft. (liters) | 9.6 (270) | CYLINDER VOLUME - cu. ft. (liters) | 12.3 (350) | CYLINDER VOLUME - cu. ft. (liters) | 18.7 (530) | |
| REVERSING CYLINDER | Option | REVERSING CYLINDER | Option | REVERSING CYLINDER | Option | DOOR OPENING SIZE - in (mm) | 26.9 (683) | |
| DOOR OPENING SIZE - in (mm) | 22.7 (576) | DOOR OPENING SIZE - in (mm) | 22.7 (576) | DOOR OPENING SIZE - in (mm) | 22.7 (576) | ENERGY DATA | Gas Models - Per Pocket | |
| ENERGY DATA | Gas Models - Per Pocket | 64,000 Btu/hr | Gas Models - Per Pocket | 73,000 Btu/hr | Gas Models - Per Pocket | 90,000 Btu/hr | 130,000 Btu/hr | |
| | Steam Models - Per Pocket | 83,500 Btu/hr | Steam Models - Per Pocket | 83,500 Btu/hr | Steam Models - Per Pocket | 103,400 Btu/hr | 113,600 Btu/hr | |
| | Electric Models | 12kW | Electric Models | 21kW | Electric Models | 24kW | Electric Models | 30kW |
| GAS CONNECTIONS - in (npt) | 0.5 | GAS CONNECTIONS - in (npt) | 0.5 | GAS CONNECTIONS - in (npt) | 0.5 | GAS CONNECTIONS - in (npt) | 0.5 | |
| PLUMBING CONNECTIONS - STEAM - in (npt) | 0.75 | PLUMBING CONNECTIONS - STEAM - in (npt) | 0.75 | PLUMBING CONNECTIONS - STEAM - in (npt) | 0.75 | PLUMBING CONNECTIONS - STEAM - in (npt) | 0.75 | |
| AIR OUTLET - in (mm) | 6 (152) | AIR OUTLET - in (mm) | 6 (152) | AIR OUTLET - in (mm) | 8 (200) | AIR OUTLET - in (mm) | 8 (200) | |
| MOTOR - hp | Fan | 0.5 | MOTOR - hp | Fan | 0.5 | MOTOR - hp | Fan | 0.5 |
| | Cylinder | 0.3 | MOTOR - hp | Cylinder | 0.3 | MOTOR - hp | Cylinder | 0.5 |
| AIRFLOW - cfm | 500 | AIRFLOW - cfm | 500 | AIRFLOW - cfm | 600 | AIRFLOW - cfm | 700 | |
| ELECTRICAL SPECS - amps | Gas & Steam | | Gas & Steam | | Gas & Steam | | Gas & Steam | |
| | B | 100-120V/50/60/1 | 10 | B | 100-120V/50/60/1 | 10 | B | 100-120V/50/60/1 |
| | X | 200-240V/50/60/3 | 6 | X | 200-240V/50/60/3 | 6 | X | 200-240V/50/60/3 |
| | N | 440-480V/50/60/3 | 3 | N | 440-480V/50/60/3 | 3 | N | 440-480V/50/60/3 |
| | P | 380-415V/50/60/3 | 3 | P | 380-415V/50/60/3 | 3 | P | 380-415V/50/60/3 |
| | Electric | | Electric | | Electric | | Electric | |
| | D | 200-208V/50/60/1 | 60 | D | 200-208V/50/60/1 | 104 | D | 200-208V/50/60/1 |
| | E | 230-240V/50/60/1 | 55 | E | 230-240V/50/60/1 | 90 | E | 230-240V/50/60/1 |
| | F | 200-208V/50/60/3 | 36 | F | 200-208V/50/60/3 | 61 | F | 200-208V/50/60/3 |
| | G | 230-240V/50/60/3 | 32 | G | 230-240V/50/60/3 | 52 | G | 230-240V/50/60/3 |
| | H | 380V/50/60/3 | 19 | H | 380V/50/60/3 | 33 | H | 380V/50/60/3 |
| | J | 400-415V/50/60/3 | 18 | J | 400-415V/50/60/3 | 30 | J | 400-415V/50/60/3 |
| | K | 440V/50/60/3 | 17 | K | 440V/50/60/3 | 29 | K | 440V/50/60/3 |
| L | 460-480V/50/60/3 | 15 | L | 460-480V/50/60/3 | 27 | L | 460-480V/50/60/3 | |
| SHIPPING DIMENSIONS | Width | 30 (760) | Width | 30 (760) | Width | 33 (840) | Width | 41.5 (1050) |
| | Depth | 43 (1090) | Depth | 49 (1240) | Depth | 49 (1240) | Depth | 50 (1270) |
| | Height | 67.6 (1720) | Height | 67.6 (1720) | Height | 67.6 (1720) | Height | Gas & Electric - B1 (2060) Steam - B3.5 (2120) |
| NET WEIGHT - lb (kg) | Gas & Steam | 300 (135) | NET WEIGHT - lb (kg) | Gas & Steam | 320 (145) | NET WEIGHT - lb (kg) | Gas | 650 (295) |
| SHIPPING WEIGHT - lb (kg) | Electric | 330 (144) | Electric | 330 (150) | Electric | 350 (160) | Electric | 690 (315) |
| | Gas & Steam | 310 (140) | Gas & Steam | 320 (155) | Gas & Steam | 360 (165) | Gas | 700 (320) |
| AGENCY APPROVALS | Electric | 330 (150) | Electric | 350 (160) | Electric | 370 (170) | Electric | 740 (335) |
| | CSA | CSA | CSA | CSA | CSA | CSA | Steam | 730 (330) |

| MODEL | HT055 | MODEL | HT075 | | | |
|------------------------------------|---------------------------|---|---------------------------|---|------------------|-----|
| CONTROL OPTION | Galaxy, Dual Digital | CONTROL OPTION | Galaxy, Dual Digital | | | |
| CAPACITY - lb (kg) | 55 (25) | CAPACITY - lb (kg) | 75 (34) | | | |
| OVERALL WIDTH - in (mm) | 34.5 (876) | OVERALL WIDTH - in (mm) | 38.5 (980) | | | |
| OVERALL DEPTH - in (mm) | 53.1 (1350) | OVERALL DEPTH - in (mm) | 53 (1350) | | | |
| OVERALL HEIGHT - in (mm) | 66.7 (1700) | OVERALL HEIGHT - in (mm) | 77.3 (1960) | | | |
| CYLINDER DIAMETER - in (mm) | 33 (838) | CYLINDER DIAMETER - in (mm) | 37 (940) | | | |
| CYLINDER DEPTH - in (mm) | 35 (889) | CYLINDER DEPTH - in (mm) | 36 (914) | | | |
| CYLINDER VOLUME - cu. ft. (liters) | 17.3 (490) | CYLINDER VOLUME - cu. ft. (liters) | 22.4 (634) | | | |
| REVERSING CYLINDER | Option | DOOR OPENING SIZE - in (mm) | 26.9 (683) | | | |
| DOOR OPENING SIZE - in (mm) | 26.9 (683) | ENERGY DATA | Gas Models - Per Pocket | | | |
| ENERGY DATA | Gas Models - Per Pocket | 112,000 Btu/hr | Steam Models - Per Pocket | 165,000 Btu/hr | | |
| | Steam Models - Per Pocket | 133,000 Btu/hr | Electric Models | 27kW | | |
| | Electric Models | 27kW | Electric Models | 36kW | | |
| GAS CONNECTIONS - in (npt) | 0.5 | GAS CONNECTIONS - in (npt) | 0.5 | | | |
| AIR OUTLET - in (mm) | 8 (200) | PLUMBING CONNECTIONS - STEAM - in (npt) | 0.75 | | | |
| MOTOR - hp | Fan | 0.5 | AIR OUTLET - in (mm) | 8 (200) | | |
| | Cylinder | 0.5 | MOTOR - hp | Fan | 0.5 | |
| AIRFLOW - cfm | Gas | 700 | MOTOR - hp | Cylinder | 0.5 | |
| | Electric | 800 | AIRFLOW - cfm | Gas | 800 | |
| ELECTRICAL SPECS - amps | Gas & Steam | | Gas & Steam | | | |
| | B | 100-120V/50/60/1 | 12 | B | 100-120V/50/60/1 | 12 |
| | X | 200-240V/50/60/3 | 7 | X | 200-240V/50/60/3 | 7 |
| | N | 440-480V/50/60/3 | 3 | N | 440-480V/50/60/3 | 3 |
| | P | 380-415V/50/60/3 | 3 | P | 380-415V/50/60/3 | 3 |
| | Electric | | Electric | | | |
| | D | 200-208V/50/60/1 | 133 | D | 200-208V/50/60/1 | 104 |
| | E | 230-240V/50/60/1 | 116 | E | 230-240V/50/60/1 | 90 |
| | F | 200-208V/50/60/3 | 78 | F | 200-208V/50/60/3 | 56 |
| | G | 230-240V/50/60/3 | 67 | G | 230-240V/50/60/3 | 52 |
| | H | 380V/50/60/3 | 42 | H | 380V/50/60/3 | 49 |
| | J | 400-415V/50/60/3 | 39 | J | 400-415V/50/60/3 | 45 |
| | K | 440V/50/60/3 | 37 | K | 440V/50/60/3 | 45 |
| L | 460-480V/50/60/3 | 34 | L | 460-480V/50/60/3 | 34 | |
| SHIPPING DIMENSIONS | Width | 35.5 (900) | Width | 41.5 (1050) | | |
| | Depth | 57 (1450) | Depth | 56 (1420) | | |
| | Height | 70.5 (1790) | Height | Gas & Electric - B1 (2060) Steam - B3.5 (2120) | | |
| NET WEIGHT - lb (kg) | Gas & Steam | 430 (195) | NET WEIGHT - lb (kg) | Gas | 680 (310) | |
| SHIPPING WEIGHT - lb (kg) | Electric | 440 (200) | Electric | 710 (320) | | |
| | Gas & Steam | 470 (215) | Gas | 730 (330) | | |
| AGENCY APPROVALS | Electric | 480 (220) | Electric | 760 (340) | | |
| | CSA | CSA | Steam | 770 (350) | | |

Tumble dryer models are made to suit a variety of electrical service characteristics. See your Huebsch distributor for specifications. For further details on installation, refer to installation, operation and maintenance instructions supplied with the tumble dryer. Amperage ratings available in installation manual.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design specifications subject to change without notice. The quality management system of Alliance Laundry Systems has been registered to ISO 9001.

Huebsch Distributor DC, DE, MD, PA, VA & WV



LES
Laundry Equipment Services

Call us Mon-Fri 8 AM - 5 PM
1-800-866-6905
Email: info@leslaundry.com