

## On- Premises 20-70 lb Softmount Washer-Extractor



Maximized throughput, minimized costs. That's what busy on-premises laundries demand. Huebsch® softmount washer-extractors deliver those results, while producing exceptional finished wash quality. In addition, their durability ensures the machines will be consistent laundry performers for years to come.

### Strength

A heavy-duty suspension system absorbs vibrations without the need for special foundations. Reinforced stainless steel side panels and oversized door and hinges contribute to durability and a long life for the machine.

### Power

High G-Force extraction speeds of between 350 and 400 G-Force deliver exceptional power to remove more water from loads and reduce drying time – combining for increased throughput.

### Performance

Available in a variety of capacities, including 20 lb, 25 lb, 30 lb, 40 lb, 55 lb, 70 lb, 90 lb and 125 lb Huebsch has a softmount washer-extractor model to meet the needs of any on-premises laundry.



### HC200

The HC200 Control provides up to 99 cycle programs. Versatile and easy to use, the advanced computer control meets a variety of specialized needs. With more than 20 languages available, our HC200 is intuitive for bilingual operators. Users can easily follow the status of every phase of the wash cycle and modify data and parameters at any time to monitor for maximum efficiency.

visit [huebsch.com](http://huebsch.com)

# On-Premises Softmount Washer/Extractor Specifications

MODEL		HY020	HY025	HY030	HY040	HY055	HY070
CONTROL OPTION		HC200	HC200	HC200	HC200	HC200	HC200
CAPACITY - lb (kg)		20 (8)	25 (11)	30 (14)	40 (18)	55 (24)	70 (28)
OVERALL WIDTH - in (mm)		27.95 (710)	31.29 (795)	31.29 (795)	38.18 (970)	38.18 (970)	38.18 (970)
OVERALL DEPTH - in (mm)		31.1 (790)	31.29 (795)	37.2 (945)	38.18 (970)	43.5 (1105)	46.65 (1185)
OVERALL HEIGHT - in (mm)		43.89 (1115)	48.22 (1225)	48.22 (1225)	55.51 (1410)	55.51 (1410)	55.51 (1410)
CYLINDER DIAMETER - in (mm)		20.87 (530)	24.40 (620)	24.4 (620)	29.53 (750)	29.53 (750)	29.53 (750)
CYLINDER DEPTH - in (mm)		13.78 (350)	13.78 (350)	17.72 (450)	16.14 (410)	21.46 (545)	24.41 (620)
CYLINDER VOLUME - cu. ft. (liters)		2.6 (75)	3.7 (105)	4.8 (135)	6.4 (180)	8.5 (240)	9.9 (280)
DOOR OPENING SIZE - in (mm)		13 (330)	16.14 (410)	16.14 (410)	18.11 (460)	18.11 (460)	18.11 (460)
DOOR BOTTOM TO FLOOR - in (mm)		13.74 (349)	13.46 (342)	13.46 (342)	18.77 (477)	18.77 (477)	18.77 (477)
WASH SPEED - RPM		49	49	49	42	42	42
EXTRACT SPEED - RPM		1165	1075	1075	980	980	915
EXTRACT G-FORCE		400	400	400	400	400	350
WATER INLET CONNECTION - in (mm)		2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)
STEAM INLET CONNECTION - in (mm)		0.5 (13)	0.5 (13)	0.5 (13)	0.5 (13)	0.5 (13)	0.5 (13)
DRAIN DIAMETER - in (mm)		3 (76)	3 (76)	3 (76)	3 (76)	3 (76)	3 (76)
MOTOR POWER CONSUMPTION - hp (kw)		1.00 (.75)	1.48 (1.10)	2.01 (1.50)	2.95 (2.20)	4.02 (3.00)	4.02 (3.00)
VOLTAGE/ CIRCUIT BREAKER - FLA*	200-240/50/60/1/3**	10-6.7 (1 Ph)	15-9.8 (1 Ph)	15-10.1 (1 Ph)	20-14.2 (1 Ph)	20-15 (1 Ph)	20-16 (1 Ph)
		10-6.7 (3 Ph)	15-9.8 (3 Ph)	15-10.1 (3 Ph)	20-14.2 (3 Ph)	20-15 (3 Ph)	20-16 (3 Ph)
SHIPPING DIMEN- SIONS APPROX. - in (mm)	Width	29.53 (750)	32.87 (835)	32.87 (835)	40.35 (1025)	10-71	10-72
	Depth	33.01 (840)	33.01 (840)	38.78 (985)	39.96 (1015)	40.35 (1025)	40.35 (1025)
	Height	49.02 (1245)	52.95 (1345)	52.95 (1345)	61.02 (1550)	45.28 (1150)	48.23 (1225)
NET WEIGHT - lb (kg)		408 (185)	463 (210)	563 (255)	838 (380)	61.02 (1550)	61.02 (1550)
SHIPPING WEIGHT - lb (kg)		441 (200)	518 (235)	606 (275)	871 (395)	948 (430)	1092 (495)
AGENCY APPROVALS		CSA	CSA	CSA	CSA	992 (450)	1135 (515)
						CSA	CSA

Information shown applies to highest end control available.

Note: Not all options are available for all models. Twelfth digit in model number indicates US or Canadian unit. C=Canada & T=US.

Refer to the price list for the available models and options.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous improvements. Design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.

**Huebsch Distributor DC, DE, MD, PA, VA & WV**



**LES**  
Laundry Equipment Services

**Call us Mon-Fri 8 AM - 5 PM**  
**1-800-866-6905**  
**Email: info@leslaundry.com**