

Vended **30 lb - 75 lb**
Stack Tumble Dryer



VENDED 30- AND 45-LB STACK TUMBLE DRYERS

At Huebsch, our priority is making commercial laundry equipment that's perfectly aligned with your business philosophy. In other words, because you believe that profit is the inevitable result of superior efficiency, durability, simplicity and service, that's exactly what we deliver.

What's more, we deliver it in every facet of our products...

UNMATCHED DURABILITY

Built with premium materials and tested to meet the demands of the harshest environments, these commercial-grade machines deliver reliable, efficient operation load after load—and they're backed by Huebsch's standard three-year warranty.*

*Parts only, labor not included. See Huebsch Warranty Bond for specifics.



HUEBSCH COMMAND™

Laundromat data and analytics that are custom-made for the way you operate

Huebsch Command lets you use all features of Galaxy™ controls—but now you can access them remotely, from anywhere in the world with an internet connection!



visit huebsch.com

* Not all models are available in all markets. In order to highlight key details, machine images do not adhere to a standard scale.

Vended **Stack & Single Tumble Dryer** Specifications

Models	HTT30	HTT45	HT050	HT075
Control Options	Galaxy™ Touch/600	Galaxy™ Touch/600	Galaxy™ Touch/600	Galaxy™ Touch/600
Capacity – lb (kg)	30 (13) x 2	45 (20) x 2	50 (25)	75 (34)
Width – in (mm)	31.5 (800)	34.5 (875)	38.5 (980)	38.5 (980)
Depth – in (mm)	43.6 (1110)	49.5 (1260)	46.8 (1190)	53.0 (1350)
Height – in (mm)	76.3 (1940)	81.3 (2065)	77.3 (1960)	77.3 (1960)
Cylinder Diameter – in (mm)	30.0 (762)	33.0 (838)	37.0 (940)	37.0 (940)
Cylinder Depth – in (mm)	26.0 (660)	30.0 (762)	30.0 (762)	36.0 (914)
Cylinder Volume – cu ft (liters)	10.6 (300)	14.8 (420)	18.7 (530)	22.4 (634)
Reversing Cylinder	Standard	Standard	Standard	Standard
Door Opening Size – in (mm)	22.6 (574)	26.9 (683)	26.9 (683)	26.9 (683)
Heat Input Power - Per Pocket – Btu/hr	73,000 x 2	95,000 x 2	130,000	165,000
Gas Connections* – in (mm)	0.5	0.5	0.5	0.5
Air Outlet – in (mm)	1 x 8 (200) Oval	1 x 10 (250) Oval	8 (200)	8 (200)
Motor - HP	Fan	2 x 0.5	0.5	0.5
	Cylinder	2 x 0.5	0.5	0.5
Airflow – cfm (liters/sec)	2 x 400 (380)	2 x 600 (285)	700 (330)	800 (380)
Electrical Specs - amps	(B) 100-120V/50/60/1	16	20	9
	(X) 200-240V/50/60/1/3	9	12	6
Shipping Dimensions Approx. – in (mm)	Width	32.5 (830)	35.5 (900)	41.5 (1050)
	Depth	47.0 (1190)	54.0 (1370)	50.0 (1270)
	Height	79.9 (2030)	84.9 (2160)	81.0 (2060)
Net Weight – lb (kg)	580 (265)	690 (315)	660 (300)	715 (324)
Shipping Weight – lb (kg)	615 (280)	735 (335)	715 (324)	760 (345)
Agency Approvals	CSA	CSA	CSA	CSA

Tumble dryer models are made to suit a variety of electrical service characteristics. See your Huebsch distributor for specifications. For further details on installation, refer to installation, operation and maintenance instructions supplied with the tumble dryer. Amperage ratings available in installation manual.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design specifications subject to change without notice. The quality management system of Alliance Laundry Systems has been registered to ISO 9001.

Huebsch Distributor DC, DE, MD, PA, VA & WV



LES
Laundry Equipment Services

Call us Mon-Fri 8 AM - 5 PM
1-800-866-6905
Email: info@leslaundry.com