

## Vended **Galaxy™ Touch** Softmount Washer-Extractor



Huebsch's softmount washer-extractors, featuring Galaxy™ Touch control, is a unique product that truly delivers return on investment.

- Contemporary aesthetic for a more premium retail experience
- Strong frame lasts longer, balances loads more efficiently, and is designed to reduce sound and vibration levels
- Advanced inverter drive system provides smooth, reliable performance
- High extraction speeds mean shorter dry times and lower energy bills
- Easily serviceable with front panel access

### Galaxy™ Touch Control

The Galaxy™ Touch display is clear, easy to use, easy to understand directions with profitable cycle modifiers enhance your customers' experience and increase return on investment.

- 7", full color, touch screen display
- User-friendly screens with operating instructions built in as part of the control
- 3 basic cycles, 1 custom cycle, 3 basic temperature options
- Easy-to-understand cycle modifier prompts will encourage your customers to customize their wash
- Flexible pricing and additional revenue opportunities with customizable cycle modifiers, time-of-day pricing and lucky cycle options
- 30+ languages available
- On-screen timer so your customers know exactly how much time their cycle will take



- Speed Cycle option for those who want to get in and out quickly
- Flexible Payment Options – Coin, Card, Mobile, Cash

visit [huebsch.com](http://huebsch.com)

## Vended **Softmount Washer-Extractor** Specifications

Models	HYT020	HYT030	HYT040	HYT055	HYT070	
Control Options	Galaxy™ Touch	Galaxy™ Touch	Galaxy™ Touch	Galaxy™ Touch	Galaxy™ Touch	
Capacity – lb (kg)	20 (9)	30 (14)	40 (18)	55 (25)	70 (32)	
Overall Width – in (mm)	27.95 (710)	31.29 (795)	38.18 (970)	38.18 (970)	38.18 (970)	
Overall Depth – in (mm)	30.71 (780)	36.81 (935)	37.80 (960)	43.11 (1095)	46.26 (1175)	
Overall Height – in (mm)	44.69 (1135)	49.02 (1245)	56.30 (1430)	56.30 (1430)	56.30 (1430)	
Cylinder Diameter – in (mm)	20.87 (530)	24.40 (620)	29.53 (750)	29.53 (750)	29.53 (750)	
Cylinder Depth – in (mm)	13.78 (350)	17.72 (450)	16.14 (410)	21.46 (545)	24.41 (620)	
Cylinder Volume – cu ft (liters)	2.6 (75)	4.8 (135)	6.4 (180)	8.5 (240)	9.9 (280)	
Door Opening Size – in (mm)	13 (330)	16.14 (410)	18.11 (460)	18.11 (460)	18.11 (460)	
Door Bottom to Floor – in (mm)	13.74 (349)	13.46 (342)	18.77 (477)	18.77 (477)	18.77 (477)	
Water Inlet Connection – in (mm)	2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)	
Drain Diameter – in (mm)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	
Drain Height to Floor – in (mm)	3.46 (88)	3.46 (88)	4.27 (108.5)	4.27 (108.5)	4.27 (108.5)	
Motor Power Consumption – HP(kW)	1 (0.75)	2.01 (1.5)	2.95 (2.20)	4.02 (3.0)	4.02 (3.0)	
Wash Speed - RPM	49	49	42	42	42	
Extract Speed - RPM	1165	1075	980	980	915	
Extract G-Force	400	400	400	400	350	
* Voltage/ Circuit Breaker - FLA	208-240/60/1	10-6.7	15-10.1	20-14.2	20-15	20-16
	440-480/60/3	–	–	–	10-7.1	10-7.2
Shipping Dimensions Approx. – in (mm)	Width	29.53 (750)	32.87 (835)	40.35 (1025)	40.35 (1025)	40.35 (1025)
	Depth	33.01 (840)	38.78 (985)	39.96 (1015)	45.28 (1150)	48.23 (1225)
	Height	49.80 (1265)	53.75 (1365)	61.81 (1570)	61.81 (1570)	61.81 (1570)
Net Weight – lb (kg)	408 (185)	563 (255)	838 (380)	948 (430)	1092 (495)	
Shipping Weight – lb (kg)	441 (200)	606 (275)	871 (395)	992 (450)	1135 (515)	
Agency Approvals	CSA	CSA	CSA	CSA	CSA	

\*Circuit breaker and amp draw data shown are for models without electric heat. Consult factory for other configurations. Manufacturer strongly recommends using a circuit breaker instead of fuses.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.

**Huebsch Distributor DC, DE, MD, PA, VA & WV**



**LES**  
Laundry Equipment Services

**Call us Mon-Fri 8 AM - 5 PM**  
**1-800-866-6905**  
**Email: info@leslaundry.com**