



Vended 20 lb - 100 lb Hardmount Washer

GALAXY™ 600: THE PINNACLE OF CONVENIENCE & CONTROL

Galaxy controls make life easier for both laundromat owners and customers with intuitive operation, simple programming and easy-to-understand diagnostics and reports. Your laundry is selling convenience and a high-quality wash and dry. With Huebsch Galaxy™ 600 controls, your laundromat gives customers a user-friendly platform and the flexibility to tailor cycles the way they like. Best of all, that flexibility brings additional revenue-generating opportunities.

CONTROL AESTHETICS OPTIONS



WASHER-EXTRACTOR CONTROL



TUMBLE DRYER CONTROL



Galaxy™ 600 benefits include:

- 200 G-Force final extract to reduce drying times, lower utility bills and increase customer satisfaction
- 24 Wash cycle combinations for customers to choose from
- Multi-level vend and cycle modifiers to increase revenue
- Four optimized drying cycles
- Time-of-day pricing to help manage peak-period business and attract new customers
- Digital display keeps customers aware of the cycle time remaining
- Huebsch Command™ compatible for remote management ease



visit huebsch.com

* Not all models are available in all markets. In order to highlight key details, machine images do not adhere to a standard scale.

Vended Hardmount Washer-Extractor Specifications

Models	HCT020	HCT030	HCT040	HCT060	HCT080	HCT100	
Control Options	Galaxy™ Touch/600	Galaxy™ Touch/600	Galaxy™ Touch/600	Galaxy™ Touch/600	Galaxy™ Touch/600	Galaxy™ Touch/600	
Capacity – lb (kg)	20 (9)	30 (13.6)	40 (18)	60 (27)	80 (36)	100 (45)	
Overall Width – in (mm)	26 (660)	29 (737)	30.6 (777)	34.1 (866)	41.5 (1054)	41.5 (1054)	
*Overall Depth – in (mm)	30.9 (785)	35.3 (892)	42.3 (1074)	44.7 (1135)	47.1 (1196)	51 (1298)	
Overall Height – in (mm)	43 (1092)	45 (1143)	47.2 (1199)	49.9 (1267)	57.2 (1453)	57.2 (1453)	
Cylinder Diameter – in (mm)	21 (533)	24 (610)	26.3 (668)	30 (762)	36 (914)	36 (914)	
Cylinder Depth – in (mm)	13.6 (351)	16 (406)	20.3 (516)	22 (559)	21.9 (556)	25.9 (658)	
Cylinder Volume – cu ft (liters)	2.8 (79)	4.2 (119)	6.3 (178)	9 (225)	12.9 (365)	15.2 (430)	
Door Opening Size – in (mm)	11.8 (295)	14.3 (363)	16.3 (414)	16.3 (414)	18.5 (470)	18.5 (470)	
Door Bottom to Floor – in (mm)	14.4 (366)	14 (356)	14.6 (371)	14.9 (378)	17.9 (455)	17.9 (455)	
Water Inlet Connection – in (mm)	2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)	4 x 0.75 (19)	4 x 0.75 (19)	4 x 0.75 (19)	
Drain Diameter – in (mm)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	
Drain Height to Floor – in (mm)	3.9 (99)	4.3 (109)	4.5 (114)	4.9 (124)	5.1 (130)	5.1 (130)	
Motor Power Consumption – HP(kW)	1 (0.75)	1 (0.75)	2 (1.5)	3 (2.2)	5 (3.7)	5 (3.7)	
Total # of Speeds	5, 9	6, 9	6, 9	5, 9	6, 9	6, 9	
Cylinder Speeds – RPM (G-Force)	Gentle	37 (0.4)	34 (0.4)	33 (0.4)	31 (0.4)	28 (0.4)	
	Wash	51 (0.8)	48 (0.8)	46 (0.8)	43 (0.8)	39 (0.8)	
	Distribution	92 (2.5)	86 (2.5)	82 (2.5)	77 (2.5)	70 (2.5)	
	Very Low	301 (2.7)	282 (2.7)	269 (2.7)	252 (2.7)	230 (2.7)	
	Low	518 (80)	485 (80)	464 (80)	434 (80)	396 (80)	
	Medium	379 (100)	342 (100)	318 (100)	285 (100)	243 (900)	
	High	648 (125)	606 (125)	579 (125)	542 (125)	495 (125)	
	Ultra High	710 (150)	664 (150)	635 (150)	594 (150)	542 (150)	
Voltage/ Circuit Breaker – FLA	B	120/60/1	15-9	15-12	20-15	N/A	
	X	200-240/50-60/3	15-4 (1 Ph) 15-3 (3 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	15-11 (1 Ph) 15-7 (3 Ph)	20-16 (1 Ph) 15-9 (3 Ph)
	Y	200-240/60/3 (Pump Drain Only)	15-4 (1 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	N/A	N/A
Shipping Dimensions Approx. – in (mm)	Width	28 (711)	31.5 (800)	32.5 (826)	37.5 (953)	44 (1118)	
	Depth	33.8 (859)	38.3 (973)	43.5 (1105)	46.9 (1191)	54.5 (1384)	
	Height	49.4 (1255)	51.3 (1303)	53.6 (1361)	56.3 (1430)	59.6 (1514)	
Net Weight – lb (kg)	340 (154)	440 (200)	540 (243)	680 (308)	1250 (567)	1280 (581)	
Shipping Weight – lb (kg)	380 (172)	480 (218)	580 (263)	720 (327)	1300 (590)	1350 (603)	
Slat Crate Shipping Weight – lb (kg)	460 (209)	580 (263)	680 (308)	840 (381)	1430 (649)	1460 (662)	
***Agency Approvals	cULce	cULce	cULce	cULce	cULce	cULce	

*Overall depth includes vacuum breaker to door handle.

** Circuit breaker and amp draw data shown are for models without electric heat. Consult factory for other configurations. Manufacturer strongly recommends using a circuit breaker instead of fuses. Use 3-pole circuit breakers for 3-phase machines.

***Agency approvals may vary depending on configuration. Steam connection requires 1/2" N.P.T.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.

Huebsch Distributor DC, DE, MD, PA, VA & WV



LES
Laundry Equipment Services

Call us Mon-Fri 8 AM - 5 PM
1-800-866-6905
Email: info@leslaundry.com