

## Vended 30 lb - 75 lb Tumble Dryers



### VENDED 30, 55 AND 75 LB TUMBLE DRYERS

At Huebsch, our priority is making commercial laundry equipment that's perfectly aligned with your business philosophy. In other words, because you believe that profit is the inevitable result of superior efficiency, durability, simplicity and service, that's exactly what we deliver.

What's more, we deliver it in *every* facet of our products...

#### INVEST IN ADVANTAGE

Huebsch tumble dryers maximize profits through superior engineering

##### Higher capacity

Efficiency means drying more loads, faster. That's how Huebsch tumble dryers—offered in 25-, 30-, 35- and 55-lb models—are built to operate. Even our 25-lb model boasts a 7.7 cu ft cylinder to dry large loads.

##### Optimum efficiency

Huebsch tumble dryers feature an innovative axial airflow process, reducing energy consumption and producing some of the industry's fastest dry times. Faster drying means less time spent at the laundromat and increased customer satisfaction, loyalty and store profits.

##### Collaborative effort

Huebsch tumble dryers are available in both single and stack pocket configurations to give your store more drying options and make the most of your space.

visit [huebsch.com](http://huebsch.com)

## Vended 30-75 lb Tumble Dryer Specifications

Models	HT030	HT055	HT075
Control Options	Galaxy™ Touch/600	Galaxy™ Touch/600	Galaxy™ Touch/600
Capacity – lb (kg)	30 (13)	55 (24)	75 (34)
Width – in (mm)	27.9 (710)	34.5 (876)	38.5 (980)
Depth – in (mm)	45.5 (1155)	53.1 (1350)	53.0 (1350)
Height – in (mm)	63.9 (1625)	66.7 (1700)	77.3 (1960)
Cylinder Diameter – in (mm)	26.5 (673)	33 (838)	37.0 (940)
Cylinder Depth – in (mm)	31.8 (810)	35.0 (889)	36.0 (914)
Cylinder Volume – cu ft (liters)	9.6 (270)	17.3 (490)	22.4 (634)
Reversing Cylinder	Standard	Standard	Standard
Door Opening Size – in (mm)	22.7 (577)	26.9 (683)	26.9 (683)
Heat Input Power - Per Pocket – Btu/hr	73,000	112,000	165,000
Gas Connections* – in (mm)	0.5	0.5	0.5
Air Outlet – in (mm)	6 (150)	8 (200)	8 (200)
Motor - HP	Fan	0.5	0.5
	Cylinder	0.5	0.5
Airflow – cfm (liters/sec)	500 (240)	700 (330)	800 (380)
Electrical Specs - amps	(B) 100-120V/50/60/1	10	12
	(X) 200-240V/50/60/1/3	6	7
Shipping Dimensions Approx. – in (mm)	Width	30.0 (760)	35.5 (900)
	Depth	49.0 (1240)	57 (1450)
	Height	67.6 (1720)	70.5 (1790)
Net Weight – lb (kg)	335 (152)	438 (199)	715 (324)
Shipping Weight – lb (kg)	368 (167)	478 (217)	760 (345)
Agency Approvals	CSA	CSA	CSA

\* LP gas available for 75 lb capacity only. Field conversion kits available for other capacities.

Tumble dryer models are made to suit a variety of electrical service characteristics. See your Huebsch distributor for specifications. For further details on installation, refer to Installation, Operation and Maintenance Instructions supplied with the tumble dryer. USA and Canada models are certified by CSA International.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems of Alliance Laundry Systems are registered to ISO 9001.

Tumble dryer models are made to suit a variety of electrical service characteristics. See your Huebsch distributor for specifications. For further details on installation, refer to installation, operation and maintenance instructions supplied with the tumble dryer. Amperage ratings available in installation manual.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design specifications subject to change without notice. The quality management system of Alliance Laundry Systems has been registered to ISO 9001.

**Huebsch Distributor DC, DE, MD, PA, VA & WV**



**LES**  
Laundry Equipment Services

Call us Mon-Fri 8 AM - 5 PM  
**1-800-866-6905**  
Email: [info@leslaundry.com](mailto:info@leslaundry.com)